



L-PAD 6X

SPECIFICATIONS

Electronic specifications

FREQUENCY RESPONSE:
10 Hz ÷ 55000 kHz

Inputs

MIC:
2

GAIN RANGE:
0 dB

MONO LINE:
4

GAIN SELECTION:
15 dB

LINE INPUT IMPEDANCE:
10 kohm

Outputs

MAIN MIX:
1

CONTROL ROOM:
Yes

FX SEND:
1

PHONES:
1

2 TRACK:
Yes

Outputs specifications

MAIN OUT IMPEDANCE:
120 ohm

MAIN OUT LEVEL:
22 dBu

AUX OUT IMPEDANCE:
120 ohm

AUX OUT LEVEL:
22 dBu



EQ	INPUT CHANNELS EQ: 2 Shelving 3	
Auxiliary sends	FX POST: 1	
Internal Effects	SEND EFFECTS: 16	
Other features	FOOTSWITCH: Yes	
Electrical specifications	POWER SUPPLY: External	VOLTAGE REQUIREMENTS: 100 V - 240 V
	POWER CONSUMPTION (MAX): 17 W	
Standard compliance	CE MARKING: Yes	
Physical specifications	CABINET/CASE MATERIAL: ABS	
Size	HEIGHT: 66 mm / 2.6 inches	WIDTH: 197 mm / 7.76 inches
	DEPTH: 281 mm / 11.06 inches	
Shipping informations	PACKAGE HEIGHT: 80 mm / 3.15 inches	PACKAGE WIDTH: 280 mm / 11.02 inches
	PACKAGE DEPTH: 200 mm / 7.87 inches	PACKAGE WEIGHT: 2.48 kg / 5.47 lbs