

DT 770 M

Dynamic Headphone

Order # 472.786



FEATURES

- Closed diffuse field headphone
- Excellent ambient noise attenuation (≥ 35 dBA)
- Superb audio quality with high sound pressure level (105 dB)
- Robust spring steel headband
- Single sided cable (straight cable, 3 m long) with in-line volume control
- Gold plated jack plug (3.5 mm) and adapter (6.35 mm)

APPLICATIONS

The DT 770 M is a closed dynamic headphone designed especially for drummers. Due to its high SPL capability and excellent ambient noise attenuation, the DT 770 M is also suitable for the monitoring of PA systems (FOH) live on stage and in studios.

The single-sided 3 m connecting cable allows easy handling for everyday use and is equipped with an in-line volume control for optimum set-up. It is fitted with a gold-plated mini stereo plug (3.5 mm) with a 1/4" (6.35 mm) adapter and is therefore suitable for use with almost all headphone amplifiers.

The rugged headband construction has been strengthened to give the headphone a very secure fit, matched with mechanical reliability.

Soft earpads that are easy to clean and adjustable, sliding earpieces ensure listening comfort during extended periods of use.

The DT 770 M provides a natural and balanced sound and exceptional quality suitable for the most demanding professional and audiophile applications.

SPARE PARTS

EDT 550 S	Ear pads, soft PVC, circumaural	Order # 407.119
BN 59-53/A	Headband pad	Order # 340.502

TECHNICAL SPECIFICATIONS

Transducer type	Dynamic
Operating principle	Closed
Nominal frequency response	5 - 30,000 Hz
Nominal impedance	80 Ω per cartridge
Nominal SPL	105 dB SPL
Nominal T.H.D	< 0.2%
Power handling capacity	100 mW
Sound coupling to ear	Circumaural
Ambient noise isolation	≥ 35 dB(A)
Nominal headband pressure	approx. 6.5 N
Weight (without cable)	300 g
Length and type of cable	3 m / straight cable
Connection	Gold plated stereo jack plug (3.5 mm) and 1/4" adapter (6.35 mm)

Germany

Theresienstr. 8
D-74072 Heilbronn
Tel. +49 (0)71 31 / 6 17-0
Fax +49 (0)71 31 / 617-224
E-mail: info@beyerdynamic.de
Internet: www.beyerdynamic.de

United States

56 Central Ave.
Farmingdale, NY 11735
Tel. +1 (631) 293-3200
Fax +1 (631) 293-3288
E-mail: salesUSA@beyerdynamic-usa.com
Internet: www.beyerdynamic-usa.com

Great Britain

17 Albert Drive
Burgess Hill RH15 9TN
Tel. +44 (0)1444 / 258 258
Fax +44 (0)1444 / 258 444
E-mail: sales@beyerdynamic.co.uk
Internet: www.beyerdynamic.co.uk